

Binding Guide

Address: Phoenix, Tucson, AZ Phone: 866-286-8904


Fax: 866-286-8960

www.creativedocumentsystems.com



Plastic Comb Binding Best Choice for Custom Binding Applications

Plastic comb binding is the perfect choice for any document that can benefit from lie-flat binding, ease of use, coordinated colors for combs and covers, or custom imprinting. Additional pages can be easily added or removed, saving you the work of producing a whole new book or document when changes occur.



Plastic Comb Punching Pattern



Plastic Coil Binding

Best Choice for Easy-to-Use Lie Flat Document

Plastic coil binding allows a book to lie completely flat when opened cover to cover. In addition, it's elastic and keeps its shape, is available in almost every PMS color to coordinate with your covers and can be easily cut to any length.


Coil Diameter Guide			
Thickness of material to be bound(including covers)	Use this diameter of g Plastic Coil	Number of sheets 80lb offset or 20lb bond	
4:1 Pitch			
1/4" 9/32" 5/16" 23/64" 3/8" 7/16" 1/2" 17/32" 9/16" 19/32" 5/8" 43/64" 23/32" 3/4" 7/8" 29/32" 1" 1 1/8" 1 3/16" 1 1/4"	6mm 7mm 8mm 9mm 10mm 11mm 12mm 13mm 14mm 15mm 16mm 17mm 18mm 20mm 22mm 23mm 23mm 25mm 28mm 30mm 30mm	5-35 36-47 48-60 61-70 71-80 81-90 91-100 101-110 111-120 121-130 131-140 141-150 151-160 161-180 181-200 201-210 211-230 231-260 261-280 281-290	

Plastic Coil Punching Pattern

• • • • • • • • • • • • •

4:1 Round

5:1 Pitch available upon request



Wire Binding

Best Choice for Traditional Binding Applications

Wire binding is an excellent permanent binding choice that creates true lie-flat documents, opened or closed. Double- O^R Wire is available in standard colors as well as custom colors. Though an 11" edge is standard, we will provide any custom length. Just tell us your binding edge length.

Double-O ^R Wire Binding Guide			
Thickness of bound materials (including covers)	Double-O ^R	Approximate # of sheets (based on 20 lb. bond)	
3:1 Pitch			
1/16" 1/8" 3/16" 1/4" 5/16" 3/8" 7/16"	3/16" 1/4" 5/16" 3/8" 7/16" 1/2" 9/16"	30 45 60 75 90 105 120	
	2:1 Pitch		
1/2" 5/8" 3/4" 7/8" 1" 1 1/8"	5/8" 3/4" 7/8" 1" 1 1/8" 1 1/4"	135 160 190 220 250 280	

Wire Punching Pattern

